

SPECIFICATIONS AND CONFIGURATIONS.

	3 LINK ARM	2 LINK ARM
Machine Weight	809 lb. / 367 kg	749 lb. / 340 kg
Max Lifting Capacity	100 lb. / 45 kg	100 lb. / 45 kg
Reach Radius	12 ft. / 3.65 m	8 ft. / 2.43 m
Max Belt Length From Arm	20 ft. / 6.09 m	24 ft. / 7.31 m
Extended System Length	14 ft. 7 in. / 4.44 m	10ft. 7 in. / 3.22 m
Height	2 ft. 7 in. / 0.78 m	2 ft. 7 in. / 0.78 m
Width	1 ft. 10 in. / 0.81 m	1 ft. 10 in. / 0.81 m
Stowed Length	6 ft. 11 in. / 2.10 m	6 ft. 8 in. / 2.03 m
Stowed Width	2 ft. 4 in. / 0.71 m	2 ft. 3 in. / 0.68 m
Head Height Clearance	2 ft. 2in. / 0.66 m	2 ft. 2 in. / 0.66 m
Battery	24V Lithium Ion, 80Ah	24V Lithium Ion, 80Ah
Battery Capacity	Up to 32 hours of continuous operation	Up to 32 hours of continuous operation
Battery Charging	Fully charged in as little as 3.5 hours; 30 minutes of charging delivers hours of productivity	Fully charged in as little as 3.5 hours; 30 minutes of charging delivers hours of productivity
Expected Battery Life	Rated for up to 10 years*	Rated for up to 10 years*
Life Cycles Per Charge	5,000+	5,000+
Belt Speed	Max 0.7 m/s	Max 0.7 m/s

*Depending on the rate of machine use and proper battery maintenance.



Scan to learn
more about the
MULE MZ100.

